

INSTALLATION GUIDE

WALL MOUNTED KITCHEN FAUCET

壁式廚房龍頭安裝說明

1. Place **Flange(with seal O-Ring)** over the thread-end of **Adapter**, apply pipe compound both to **Adapter** and 1/2 elbow, tighten the **Adapter** with **Flange** to wall.

將轉接器有牙的一端穿過法蘭蓋後，並塗上止洩膠(或止洩帶)在轉接器及牆壁內接頭的1/2NPT牙上，再將轉接器與法蘭蓋鎖緊於牆上。

2. Loosen Faucet Body inlet-end two set screws for installation.





鬆開2顆安裝在龍頭本體上的埋頭螺絲。

3. Attach with **Rubber seal Washer** into the inlet of **Faucet Body**, then put the **Faucet Body** (with **Rubber seal Washer**) to match with the **Adapter**, adjust the **Faucet Body** to vertical position, tighten two set screws evenly with **Hex Key** as figure shown.

在龍頭本體後端內孔裝上橡皮墊片，並將龍頭本體後端內孔套入已固定在牆上的轉接器組合，注意須保持龍頭出水管的垂直度，再用六角板手將兩顆埋頭螺絲鎖緊，完成外接濾水器前的安裝程序。

FIXING CONTENTS

組配件內容

<p>ⓐ Faucet Body × 1 龍頭本體</p> 	<p>ⓑ Adapter × 1 轉接器</p> 	<p>ⓒ Rubber seal Washer × 1 橡皮墊片</p> 
	<p>ⓓ Hex Key × 1 六角板手</p> 	<p>ⓔ Flange (with seal-O-Ring) × 1 法蘭蓋</p> 