

INSTALLATION INSTRUCTIONS

Angle Stop安裝說明

- Slide **Flange** onto the thread-end of **Valve**, then apply pipe compound or thread sealant tape to the thread and screw the **Valve** into wall water-outlet.

將法蘭蓋從凡而本體螺紋的末端裝入，然後在螺紋塗上膠合劑或是纏上止洩帶並鎖入牆壁的出水口。

For 1/2G Braided Hose
1/2G高壓編織管專用

Diagram illustrating the installation of a 1/2G Braided Hose. The components shown are:

- wall water-outlet (牆壁出水口 1/2G)
- Valve (凡而本體)
- Flange (法蘭蓋)
- 1/2 G
- Packings (option) (墊圈(選購))
- Hose (蛇管(選購) (option))

Part numbers for various configurations:

- 6875-Y6-80CP
- 6874-Y5-80CP
- 6874-Y6-80CP
- 6874-Y7-80CP
- 6875-YC-80CP
- 6903-Y7-80CP
- 6874-Z4-80CP
- 6874-Z5-80CP

For M10x1.0 Male Thread Braided Hose
M10x1.0外牙高壓編織管專用

Diagram illustrating the installation of an M10x1.0 Male Thread Braided Hose. The components shown are:

- M10x1.0
- Hose (option) (蛇管(選購))

Part number for this configuration:

- 6874-Y0-80CP

For 3/8 CxC Tube
3/8CxC硬管專用

Diagram illustrating the installation of a 3/8 CxC Tube. The components shown are:

- 1/2 G
- tapered sleeve (止水圈)
- Hex. Nut (六角螺帽)
- 3/8" Tube (option) (3/8"管子(選購))

Part number for this configuration:

- 6874-Y8-80CP